



**ACRYLIC CERAMIC – LOW ODOR**  
**ENVIRO-4000®**  
**GREEN TECHNOLOGY - ZERO V.O.C.**  
**EXTERIOR PRIMER and SEALER**

**PRODUCT DATA**  
**15 YEAR LIMITED MATERIAL WARRANTY**  
**#2090**  
**03/26/10**  
*superseding: 04/29/09*

**PRODUCT DESCRIPTION:**

ENVIRO-4000® Primer Sealer is a low odor, Zero V.O.C.\* (Volatile Organic Compound), high quality, insulating ceramic, exterior primer sealer. It is formulated with ceramic fillers, that provide insulating and soundproofing characteristics along with a uniform, easy to apply, flat priming finish. A high concentration of resin allows this Primer Sealer to seal most water, grease, oil, and other stains. It's performance stems from the high quantity of resin which provides for outstanding bonding, priming and sealing of most any exterior surface. ENVIRO-4000® Primer Sealer will seal most stains, but if stains persist, a compatible stain blocker must be used. When applied according to specifications, ENVIRO-4000® paint products offer a 15 YEAR LIMITED MATERIAL WARRANTY.

*\* This paint is described as "Zero V.O.C." because it doesn't contain any of the solvents that are normally used in conventional latex paints. Trace amounts of V.O.C.s may be present as residual components of other ingredients. Adding Colorant to this product will add V.O.C.s, although the total V.O.C. content will still be negligible.*

**ENVIRO-4000® PRIMER SEALER USES:**

For use on wall and trim surfaces: wood, concrete, brick, masonry, plaster, stucco and primed metal (no rust) and various other substrates.

**STAINS:**

Spot prime all stains before priming entire area. ENVIRO-4000® Primer Sealer will seal most stains. If stain persists, a compatible stain blocker must be used. Wood knots should be spot primed with shellac. Pressure treated wood must be aged at least 6 months before priming.

**SURFACE PREPARATION:**

**PREVIOUSLY PAINTED SURFACES:**

Thoroughly clean surface of dirt, oil, grease, chalk or foreign matter by scraping, sanding, scrubbing and/or rinsing. Scrape off any loose, blistering, cracking or peeling paint using a wire brush and scraper. Dull any nonporous or glossy surfaces by thorough washing with an abrasive kitchen cleaner or by scuff sanding before washing. This primer will resist mildew growth, but will not kill spores, which are nearly invisible and must be removed prior to painting. Scrub soiled, chalky or mildewed surfaces with a solution of one cup detergent, one quart household bleach and one gallon of water. Protect shrubbery and grass. Wash house from bottom up including eaves, soffit and fascia. The complete surface to be painted must be cleaned even if it looks clean, because invisible residues may cause peeling. Rinse surface thoroughly. Let dry 24 hours. Patch cracks and holes with patching paste. Spot prime patched areas before priming entire wall with a full coat of ENVIRO-4000® Primer Sealer.

**UNPAINTED SURFACES:**

**Wood:** Prime bare wood with one or two coats of Primer Sealer depending on condition of the surface. Sand weathered or discolored wood down to solid wood. Clean free of all dust, then prime. Wood knots should be spot primed with shellac. Pressure treated wood must be aged at least 6 months before it can be primed.

**Metal:** Clean surface of all grease, oil and foreign matter before priming. Rusted metal and galvanized metal must be primed with METAL-PRIME RED-OX™, a Red Iron Oxide Primer Sealer.

**Masonry:** Prime masonry before painting. New masonry must either be sealed with CHALK-FORCE™ or aged 60 days before priming.

**Plastered Walls:** Surface must be dry, cured and hard. Textured or swirl types and soft porous or powdery plaster must be treated with a solution of one pint household vinegar in one gallon of water. Repeat until surface is hard. Rinse with plain water. Let dry and apply a coat of CERAMIC SHIELD™ Primer Sealer.

**APPLICATION PROCEDURE:**

Stir well before using. Thinning is not recommended but if necessary use water sparingly. Do not apply when temperatures are below 40 degrees Fahrenheit or when humidity is very high. Apply using brush, roller or spray. When rolling, apply in an "N" pattern first, then cross roll to spread paint, and finish with light roller strokes in downward direction. Always roll or brush from untouched into wet paint areas. Allow at least 4 hours to dry before applying the first coat of ENVIRO-4000® paint.

**CLEAN UP:**

Clean up all spills, tools and overspray immediately while the coating is still wet with warm soapy water.

Ambient Temperature of 77°F and RH of 50% **TECHNICAL SPECIFICATIONS:** Rates & Times May Vary Beyond Specifications

|                      |                         |                |                         |
|----------------------|-------------------------|----------------|-------------------------|
| FINISH:              | Flat                    | SPREAD RATE:   | 250 to 350 sq.ft./gal.  |
| COLOR:               | White (Tintable)        | DRY to TOUCH:  | 2 to 4 Hours            |
| VEHICLE TYPE:        | Copolymer Emulsion      | RECOAT:        | 4 Hours                 |
| SOLIDS by WEIGHT:    | 54% +/- 2%              | CURE TIME:     | 10 to 14 Days           |
| SOLIDS by VOLUME:    | 30% +/- 2%              | SIZES:         | 1 Gal., 5 Gal., 55 Gal. |
| V.O.C.'s (averages): | 0 lbs./gal. • 0 g/liter | GALLON WEIGHT: | 11.8 lbs. +/- .3 lbs.   |

*Information presented on this Data Sheet has been compiled from sources to be reliable, and is accurate and reliable to the best of our knowledge and belief but is not guaranteed to be so.*



# MATERIALS HEALTH, SAFETY AND ENVIRONMENTAL DATA SHEET

**MSDS#:**  
**2090**

|   |   |   |
|---|---|---|
| <b>Product Identification</b>           | Product Name: <b>ENVIRO-4000™ Primer</b><br>Product Code #: <b>2090</b><br>General Usage: Exterior Latex Primer<br>General Description: Pigmented Latex Primer<br>C.A.S. Number: None Established; Mixture  |   |
| <b>Manufacturer Information</b>         | Manufacturer's Name: Nationwide Protective Coating Mfrs., Inc.<br>Address: 7106 24th Court East; Sarasota, FL 34243-3993<br>Emergency Telephone: 1-800-423-7264 or 941-753-7500<br>Information: 1-800-423-7264 or 941-753-7500<br>Web Site: www.nationwidecoatings.com E-Mail: info@natcoat.net<br>Date Effective: January 1 <sup>st</sup> , 2005 |   |
| <b>Chemical and Physical Properties</b> | Color: White<br>Physical State: Liquid<br>Boiling Point: 212 Fahrenheit<br>Specific Gravity (H <sub>2</sub> O=1): >1<br>Vapor Presence: about same as H <sub>2</sub> O<br>Percent Volatile: 43-53%<br>Evaporation Rate (Butyl Acetate=1): <1  | Odor: No Odor<br>Odor Threshold: Unknown<br>Melting Point: N/A<br>Freezing Point: 32 Fahrenheit<br>Solubility in H <sub>2</sub> O: Soluble<br>pH (undiluted): 8 to 8.5<br>Vapor Density (Air=1): <1 |
| <b>Fire Protection Information</b>      | Decomposition/Combustion:<br>Flash Point:<br>Recommended Extinguishing Media:<br>Flammable Limits:  | N/A<br>N/A; Does Not Burn<br>N/A<br>N/A   |
| <b>Storage and Reactivity</b>           | Hazardous Polymerization:<br>Storage Conditions:<br>Toxic Products Which May Form:  | Will Not Occur<br>Keep from Freezing<br>None  |
| <b>Transportation</b>                   | Hazard Classes:<br>Hazard Labels:<br>Hazard Determination:<br>Shipping Containers:<br>Shipping Class:   | None; Not Hazardous<br>Not Required<br>MSD Sheet<br>Varies<br>Class 55; Water Based Paint   |
| <b>Container Labeling</b>               | Explanation of Unique Labeling System: None Used  |   |

|                                   |  |   |
|-----------------------------------|--|---|
| <b>Health Hazard Data</b>         | <b>SHORT TERM EXPOSURE</b>   |   |
|                                   | Route of Entry:<br>Inhalation:<br>Skin:<br><br>Eyes:<br><br>Ingestion:   | Precautionary Treatment<br>Expected None<br>Expected None<br><br>Flush Immediately with large amounts of water for at least 15 minutes, holding eyelids open. Call a physician if irritation persists<br><br>Call a physician if significant amounts have been Swallowed. Give patient large amounts of water or milk for dilution. |
|                                   | <b>LONG TERM EXPOSURE</b>  |   |
|                                   | Carcinogen:<br>Target Organ Effects:<br>Other Health Hazards:  | None<br>None<br>None Known  |
| <b>Personal Protection</b>        | Respiratory Protection:<br>Protective Clothing:<br>Ventilation:<br>Other Protective Measures:<br>Eye Protection:   | No inhalation hazard expected<br>Apron to keep off Clothes<br>Local<br>None<br>Safety Glasses   |
| <b>Spill or Leak Protection</b>   | Accidental Release or Spill:<br><br>Neutralizing Chemical/Media:   | Collect liquid or solidify with absorbent package for disposal<br><br>N/A   |
| <b>Treatability</b>               | Biodegradability: With water prior to cure.<br>Influence on Biological Wastewater Treatment: None<br>Other Impacts on Wastewater Treatment: None<br>Recommended Wastewater Treatment: Dilutable<br>Constituents Interfering With or Not Amenable to Biological or Wastewater Treatment: None |   |
| <b>Recommended Waste Disposal</b> | Dispose of in accordance with Federal, State and Local guidelines.   |   |